

Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our [Historical View FAQs](#) or contact our [Customer Service](#).

## Switches, Appliance and Special Use - Component

**COMPANY**

**WENZHOU GANGYUAN ELECTRONICS CO LTD**

NO.2 YONGHE ONE ROAD

CHENGDONG STREET

YUEQING, Zhejiang 325608 China

E490151

**Investigated to ANSI/UL 61058-1**

Cat. No.	Load	Amps	Volts	Hz	Temp (°C)	Pol/ Cir	Endurance		IP	Dis (mm)	Std. SPCA	Ed.
							30C cycle	55C cycle				
<b>G10 series (G10, f/b -1,-2,-3,-4,-5 or Blank, f/b 00 ~ 99, f/b N,P,L or R, f/b -40 or -150, f/b letter(s), number(s), symbol(s) or blank. )</b>	RM	3(1)	0~125	50-60	25T105	1/1,2-2.3	-	10K	40	micro	-	-
	RM	2(1)	0~125	50-60	25T105	1/1,2-2.3	-	10K	-			
	RM	1.5(1)	0~125	50-60	25T105	1/1,2-2.3	-	10K	-			
	RM	1(0.5)	0~125	50-60	25T105	1/1,2-2.3	-	10K	-			
	RM	0.5(0.5)	0~125	50-60	25T105	1/1,2-2.3	-	10K	-			
	RM	3(1)	0~250	50-60	25T105	1/1,2-2.3	-	10K	-			
	RM	2(1)	0~250	50-60	25T105	1/1,2-2.3	-	10K	-			

	RM	1.5(1)	0~250	50-60	25T105	1/1,2-2.3	-	10K	-			
	RM	1(0.5)	0~250	50-60	25T105	1/1,2-2.3	-	10K	-			
	RM	0.5(0.5)	0~250	50-60	25T105	1/1,2-2.3	-	10K	-			
	R	0.1~3	0~125	50-60	25T105	1/1,2-2.3	-	10K	-			
	R	0.1~3	0~250	50-60	25T105	1/1,2-2.3	-	10K	-			
	R	0.1~3	0~12	DC	25T105	1/1,2-2.3	-	10K	-			
	R	0.1~3	0~24	DC	25T105	1/1,2-2.3	-	10K	-			
	R	0.1~3	0~36	DC	25T105	1/1,2-2.3	-	10K	-			
	RM	1(0.5)	125/250	50-60	25T125	1/1,2-2.3	-	10K	-			
	RM	2(1)	125/250	50-60	25T125	1/1,2-2.3	-	10K	-			
	RM	3(1)	125/250	50-60	25T125	1/1,2-2.3	-	10K	-			
	RM	1.5(1)	125/250	50-60	25T125	1/1,2-2.3	-	10K	-			
	RM	0.5(0.5)	125/250	50-60	25T125	1/1,2-2.3	-	10K	-			
	R	0.1	125/250	50/60	25T125	1/1,2-2.3	-	10K	-			
	R	1	125/250	50-60	25T125	1/1,2-2.3	-	10K	-			
	R	2	125/250	50-60	25T125	1/1,2-2.3	-	10K	-			
	R	3	125/250	50-60	25T123/125	1/1,2-2.3	-	10K	-			
	R	1.5	125/250	50-60	25T125	1/1,2-2.3	-	10K	-			
	R	0.5	125/250	50-60	25T125	1/1,2-2.3	-	10K	-			
<b>G15 Series</b>	RM	10(5)	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	00	micro	-	-

	RM	10(3)	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	RM	6(5)	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	RM	6(3)	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	RM	5(3)	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	RM	5(2)	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	RM	3(3)	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	RM	3(2)	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	RM	10(2)	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	GP	10	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	GP	6	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	GP	5	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	GP	3	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	R	10	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	R	6	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	R	5	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	R	3	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			

	R	5	36	DC	25T125	1/2-1.2, 2.2	6K	50K	-			
	R	3	36	DC	25T125	1/2-1.2, 2.2	6K	50K	-			
	R	2	36	DC	25T125	1/2-1.2, 2.2	6K	50K	-			
	hp	1/2	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	hp	1/3	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	hp	1/4	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
	hp	1/8	125-250	50-60	25T125	1/2-1.2, 2.2	6K	50K	-			
<b>G19-16, G19-10, G19-06 Series</b>	RM	0~16(4)	125	50-60	25T125	-2.3	-	50K	00	micro	-	-
	RM	0~16(4)	250	50-60	25T125	-	-	50K	-			
	GP	0~16	125	50-60	25T125	-	-	50K	-			
	GP	0~16	250	50-60	25T125	-	-	50K	-			
	R	0~16	125	50/60	25T125	-	-	50K	-			
	R	0~16	250	50/60	25T125	-	-	50K	-			
	hp	1	250	50/60	25T125	-	-	50K	-			
	hp	1	125	50/60	25T125	-	-	50K	-			
<b>G20</b>	GP	16(10)	125-250	50-60	25T125	1/2-1.2	6K	10K	00	full	-	-
	GP	16(8)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	10(8)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	10(5)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	10(3)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			

	GP	6(5)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	6(3)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	5(3)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	5(2)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	3(3)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	3(2)	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	16	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	10	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	GP	6	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	R	16	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	R	10	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	R	6	125-250	50-60	25T125	1/2-1.2	6K	50K	-			
	R	5	125-250	50/60	25T125	1/2-1.2	6K	50K	-			
	R	3	125-250	50/60	25T125	1/2-1.2	6K	50K	-			
	GP	5	125-250	50/60	25T125	1/2-1.2	6K	50K	-			
	GP	3	125-250	50/60	25T125	1/2-1.2	6K	50K	-			
<b>G20 Series</b>	RM	26(12)	125-250	50-60	25T125	1/2	6K	10K	00	micro	-	-
	RM	26(10)	125-250	50-60	25T125	1/2	6K	10K	-			
	RM	22(12)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	22(10)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	22(8)	125-250	50-60	25T125	1/2	6K	50K	-			

	RM	16(10)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	16(8)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	10(8)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	10(5)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	10(3)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	6(5)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	6(3)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	5(3)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	5(2)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	3(3)	125-250	50-60	25T125	1/2	6K	50K	-			
	RM	3(2)	125-250	50-60	25T125	1/2	6K	50K	-			
	GP	22	125-250	50-60	25T125	1/2	6K	50K	-			
	GP	16	125-250	50-60	25T125	1/2	6K	50K	-			
	GP	10	125-250	50-60	25T125	1/2	6K	50K	-			
	GP	6	125-250	50-60	25T125	1/2	6K	50K	-			
	R	26	125-250	50-60	25T125	1/2	6K	10K	-			
	R	22	125-250	50-60	25T125	1/2	6K	50K	-			
	R	16	125-250	50-60	25T125	1/2	6K	50K	-			
	R	10	125-250	50-60	25T125	1/2	6K	50K	-			
	R	6	125-250	DC	25T125	1/2	6K	50K	-			
	R	16	36	DC	25T125	1/2	6K	50K	-			
	R	10	36	DC	25T125	1/2	6K	50K	-			
	R	6	36	DC	25T125	1/2	6K	50K	-			

	R	3	36	DC	25T125	1/2	6K	50K	-			
	hp	1	125-250	50-60	25T125	1/2	6K	50K	-			
	hp	3/4	125-250	50-60	25T125	1/2	6K	50K	-			
	hp	1/2	125-250	50-60	25T125	1/2	6K	50K	-			
	hp	1/3	125-250	50-60	25T125	1/2	6K	50K	-			
	hp	1/4	125-250	50-60	25T125	1/2	6K	50K	-			
	hp	1/8	125-250	50-60	25T125	1/2	6K	50K	-			
<b>G20-01 Series</b>	R	1	125~250	50/60	25T130/55	1/1,2	-	10K	40	micro	-	-
	R	0.1	30	DC	25T130/55	1/1,2	-	10K	-			
<b>KCD1-101-AR</b>	R	10	125/250	50/60	T125	1/1-1.2	-	10K	40	full	5A	-
	R	6	250	50/60	T125	1/1-1.2	-	10K	-			

1A - The Switch body is installed inside of end product; consider for no accessible parts. When mounted in accordance with the manufactures instruction, this switch gets a protection degree of IP 40.

1B - The switch is to be employed in an end use product providing an enclosure or insulating barrier that provides Reinforced or Double Insulation over the front and rear switch enclosure Surfaces.

Marking: Company name or trademark **GANGYUAN**  **DECO**, catalog, model or part number, electrical ratings and the Recognized Component Mark,  on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2023-09-27

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“©2024 UL LLC.”